

## CALIFORNIA AIR TOOLS 10020SPCAD Ultra Quiet and Oil-Free 2.0 Hp Air Compressor in Sound Proof Cabinet w/Automatic Drain Valve



2.0 HP (Rated/Running)

10.0 Gallon Steel Tank

6.40 CFM @ 40 PSI

5.30 CFM @ 90 PSI


80% Air Drying System

The CALIFORNIA AIR TOOLS 10020DSPCAD Ultra Quiet & Oil-Free Air Compressor is designed to be one of the quietest 2.0 Hp air compressors in the industry having only 58 decibels of sound.



1





The powerful 2.0 HP motor operates at only 1680 RPM creating less noise, vibration and creating less wear.

## **ULTRA QUIET**

**ONLY 58 DB NOISE LEVEL** 

The Oil-Free Dual Piston Pump System is engineered for longevity, high performance, and durability.

The SP-9421 Motor/Pump is tested for a minimum pump life of 3000 hours before service. 30% more life before repair.

The SP Series of Ultra Quiet Air Compressor Motors have been designed to increase duty cycle and allow for longer continuous run times. \*

Large 10.0-gallon steel air tank.

This air compressor is ideal for anyone working inside (office, shop, store, warehouse, or home) where noise is a major issue.

## 80% AIR DRYER SYSTEM

The 80% Air Dryer is specially designed to remove water vapor from the air to protect sensitive tools and machinery.

To dry the air from the air compressor an Aftercooler and 80% Air Dryer are utilized.

The aftercooler is a heat exchanger for cooling the discharge air from the air compressor. The water vapor from the compressed air is condensed into liquid form and pushed into the Air Dryer.

Desiccant is contained within mesh bag inside 80% Air Dryer Tower







## FEATURES



**10020SPCAD** AUTOMATIC DRAIN VALVE (connect drain tube)







- \* Ultra Quiet Only 58 decibels
- \* Oil-Free Pump Cleaner air for better tool operation.
- Less maintenance and Costs.
- \* Two pressure control gauges
- \* Two Female Industrial "Push to Connect" quick connector airports (1/4" NPT)
- \* Easy Start Valve For Less Starting Amperage
- \* EZ-1-2321 Auto Drain Valve Factory Installed
- \* Condor Pressure Switch
- \* Thermal Overload Protector
- \* 130 PSI Maximum Pressure
- \* 110v / 60 hz
- \* Low Amp Draw 14 Amps
- \* Time to fill tank from empty to full 130 Seconds
- \* Recovery time from 100 PSI to 130 PSI 40 Seconds
- \* Duty Cycle 70/30\*
- \* Less heat which dissipates more efficiently.
- \* 10 Gal. Steel Air Tank With Soundproof Cabinet and Swivel Caster wheels
- \* L (21") x W (26") x H (32)
- \* 146 lbs
- \* 1 Year Limited Warranty
- \* Commercial Use: Refer to State & City Codes
- \* Non-ASME Air Tank
- \* Assembled in USA with global components

For more information and to watch a 10020DSPCAD product demonstration please visit California Air Tools: <u>https://www.californiaairtools.com/sound-proof-cabinet-ultra-quiet-air-compressors/cat-10020spcad/</u>

Manufactured in Mexico using global components. MODEL: 10020DSPCAD PART NUMBER: CAT-10020DSPCAD <u>www.californiaairtools.com</u> Revision A: 07-2024