



Category: Air Compressor
UPC: 850053943386

20 Gallon

2 HP Motor

125 PSI MAX

5.3 CFM
@90PSI

70 Decibels




SPECIFICATION SHEET

Model: 20020DCADC


PRODUCT OVERVIEW

The CALIFORNIA AIR TOOLS 20020DCADC Ultra Quiet, Ultra Dry Oil-Free 20 Gallon Air Compressor with 98% Air Drying System is designed to be one of the quietest 2.0 Hp air compressors in the industry having only 70 decibels of sound.



FEATURES

- The Powerful 2.0 HP motor operates at only 1680 RPM creating less noise and less wear.
- The SP Series of Ultra Quiet Air Compressor Motors have been designed to increase duty cycle and allow for longer continuous run time.
- The Oil-Free Dual Piston Pump System is engineered for high performance and durability.
- The California Air Tools EZ-1 Automatic Drain Valve has been designed to eliminate manually draining your air compressor air tank. The manually set timer allows you to set the time for both the frequency and duration of the draining process.
- The Easy Start Valve feature allows for a easier start up using less starting amps. The Easy Start Valve releases a small amount of air from the pump at start up to produce a no-load condition allowing the motor to spin freely. This no-load start up requires less amps for a easier start up in cold temperatures.



BENEFITS

The CAT-20020DCADC Air Compressor has a Oil-Free Dual Piston pump designed to have a life cycle before wear of 3000 Plus hours. The Oil-Free pump allows for use in a variety of temperatures (cold starts) and eliminates oil from being in the air.

The large 20 Gallon Horizontal Steel Air Tank is just the right size to fit under a bench, desk or cabinet. The Air Dryer is specially designed to remove up to 98% of the water vapor from the air to protect sensitive tools and machinery. To dry the air from the air compressor an Aftercooler and 98% Air Dryer are utilized.

The aftercooler is a heat exchanger for cooling the discharge air from the air compressor. The water vapor from the compressed air is condensed into liquid form and pushed into the Air Dryer. The easy to replace "Spin-On" Air Drer Cartridge has a regenerating High-Temperature Molecular Sieve Desiccant to dry the air. This Ultra Dry cartridge dryer has a life of 2-years before replacement.

Designed for the person looking for Power, 98% Dry Air with Low Dew Point Air Flow and Less Service with at Least 30% Less Noise! Ideal for Dental, Milling, Surgical, Manufacturing Clean Rooms, Restaurant and General Engineering Applications.

SPECIFICATIONS

Specification	Details
Material	Steel
Color	White
Weight	125 Pounds
Height	30.5 inches
Item Dimensions L x W x H	37.1"L x 22"W x 30.5"H
Capacity	20 Gallons
Maximum Current	14 Amps
Voltage	110 Volts
Noise Level	70 dB

FEATURES

1. **Ultra Quiet – Only 70 decibels**
2. Oil-Free Pump (Class 1) – Cleaner air for better tool operation. Less maintenance and Costs.
3. Two pressure control gauges
4. Easy Start Valve – For Less Starting Amperage
5. One – Female industrial "Push to Connect" quick connector
6. 0.01 Micron Prefilter
7. Condor Pressure Switch
8. Thermal Overload Protector
9. 125 PSI Maximum Pressure
10. 110 Volts / 60 Hertz / Single Phase

11. Low Amp Draw – 14 Amps
12. Time to fill tank from empty to full – 240 Seconds
13. Recovery time from 95 PSI to 125 PSI – 60 Seconds
14. Duty Cycle – 70/30*
15. Less heat which dissipates more efficiently
16. 20 Gallon Steel Air Tank for Commercial use.
17. L (37.1") x W/D (22") x H (30.5"),
18. Weight: 122 lbs
19. Easy to remove (spin off) 98% Dry Air Cannister; replace every 2 years or 4000 motor/pump running hours.
20. Aftercooler (condenser)
21. PDP performance range (-20' F. to -51' F.)
22. Air Quality: ISO 8573 – Class 2.3.1
23. EZ-1-2321 Auto Drain Valve Factory Installed
24. 1 Year Limited Warranty
25. Comes complete (2) Air Filters
26. Commercial Use: Refer to State & City Codes
27. Non-ASME Air Tank
28. Assembled in USA with global components

COMPATIBLE ACCESSORIES

- 16 Piece Air Hose & Air Tool Accessory Kit (CAT-376)
- California Air Tools Hybrider Flex 1/4in 25 Foot Hybrid Air Hose
- 317 Water (moisture) & Oil Separator Air Filter 1/4 NPT



Part Number	CAT- 20020DCADC
UPC	850053943386
Shipping Dimensions	48"L x 40"W x 38"H
Shipping Weight	165 lbs
Shipping Class	85
Ship Type	LTL
Cage Code	7VRJ0
HTSUS	8414.80.1685
Country of Origin	USA