



Category: Contractor Grade Air Compressor
UPC: 850053943461

5.0	Gallon
2	HP Motor
135	PSI MAX
5.3	CFM @90PSI
70	Decibels




SPECIFICATION SHEET

Model: 5020W

PRODUCT OVERVIEW

The CALIFORNIA AIR TOOLS 5020W Ultra Quiet & Oil-Free Rugged 5-Gallon Air Compressor is designed to be one of the quietest 2.0 Hp air compressors in the industry having only 70 decibels of sound and features extra large 7.6" wheels.



FEATURES

- The Powerful 2.0 HP (SP-9421) motor operates at only 1680 RPM creating less noise and less wear. Motor has been designed to increase duty cycle and allow for longer continuous run times.
- The Oil-Free Dual Piston Pump System is engineered for high performance, durability and provides up to 135 PSI.

SPECIFICATIONS AND PERFORMANCE



ULTRA QUIET & OIL-FREE, RUGGED AIR COMPRESSOR



BENEFITS

The CAT-5020W Air Compressor has a Oil-Free Dual Piston pump designed to have a life cycle before wear of 3000 Plus hours compared to other comparable air compressors with life cycles of 500 hours or less.

The Oil-Free pump allows for use in a variety of temperatures (cold starts) and uneven terrains (no oil in the pump).

The Easy Start Valve feature allows for a easier start up using less starting amps. The Easy Start Valve releases a small amount of air from the pump at start up to produce a no-load condition allowing the motor to spin freely. This no-load start up requires less amps for a easier start up in cold temperatures.

SPECIFICATIONS

Specification	Details
Material	Alloy Steel
Color	Silver
Weight	82 Pounds
Heigh	41.5 inches
Item Dimensions L x W x H	19"L x 21"W x 41.5"H
Capacity	5 Gallons
Maximum Current	14 Amps
Voltage	110 Volts
Noise Level	70 dB

FEATURES

1. **Ultra Quiet – Only 70 decibels**
2. Oil-Free Pump – Cleaner air for better tool operation. Less maintenance and Costs.
3. Protective Roll Cage
4. Easy Start Valve – For Less Starting Amperage
5. Telescope Handle for adjustable height: 19.5" To 27.5"
6. Easy to Lift and Easy to move around on Job Sites
7. Large Rugged Flatless Wheels (7.6")
8. Two pressure control gauges
9. Two – Female industrial "Push to Connect" quick connectors
10. Easy Start Valve – For Less Starting Amperage
11. Thermal Overload Protector
12. 135 PSI Maximum Pressure
13. 110v / 60 hz
14. Low Amp Draw – 14 Amps
15. Dedicated 15 amp outlet -14 gauge 25ft cord – Min. 5500 Watt Generator
16. Time to fill tank from empty to full – 60 Seconds

17. Recovery time from 95 PSI to 125 PSI – 20 Seconds
18. SP-9421 2 hp Motor-Pump (110v 60 hz)
19. Duty Cycle – 70/30*
20. Less heat which dissipates more efficiently (longer motor life)
21. L (19.0") x W/D (21") x H (41.5"),
22. Weight: 82 lbs
23. 1 Year Limited Warranty
24. Comes complete Two Air Filters
25. UL Certification pending
26. Commercial Use: Refer to State & City Codes

Product Overview:

[California Air Tools 5020W Website](#)

COMPATIBLE ACCESSORIES

- 16 Piece Air Hose & Air Tool Accessory Kit (CAT-376)
- California Air Tools Hybrider Flex 1/4in 25 Foot Hybrid Air Hose
- 317 Water (moisture) & Oil Separator Air Filter 1/4 NPT



Part Number	CAT- 5020W
UPC	850053943461
Shipping Dimensions	30"L x 30"W x 45"H
Shipping Weight	82 lbs
Shipping Class	85
Ship Type	SMALL PARCEL
Cage Code	7VRJ0
HTSUS	8414.80.1685
Country of Origin	MEXICO