



Category: 98% Air Dryer Series Air Compressor
UPC: 850004451199

20 Gallon
4 HP Motor
125 PSI MAX
10.6 CFM @90PSI
75 Decibels
98% Dry Air




SPECIFICATION SHEET

Model: 20040DCADC

PRODUCT OVERVIEW

The CALIFORNIA AIR TOOLS 20040DCADC Ultra Quiet, Ultra Dry Oil-Free 20 Gallon Air Compressor with Air Drying System is designed to be one of the quietest 4.0 Hp air compressors in the industry having only 75 decibels of sound.



FEATURES

- The Powerful Twin 2.0 HP motors operates at only 1680 RPM creating less noise and less wear.
- The SP Series of Ultra Quiet Air Compressor Motors have been designed to increase duty cycle and allow for longer continuous run times.
- The Oil-Free Dual Piston Pump System is engineered for high performance and durability.
- The Oil-Free pump allows for use in a variety of temperatures (cold starts) and eliminates oil from being in the air. The large 20 Gallon Steel Air Tank is just the right size for shop or garage. The Air Dryer is specially designed to remove up to 98% of the water vapor from the air to protect sensitive tools and machinery.

SPECIFICATIONS AND PERFORMANCE

22 Inches 37.1 Inches 30.5 Inches

ISO
PDP performance range (-20° F. to -51° F.)
Air Quality: ISO 8573 - Class 2.3.1

Weight 170 Pounds	Noise Level 75 Decibels	Maximum Pressure 125 PSI
Voltage 220 Volt / 60 Hertz Single Phase (No 208 Volts)	Low Amp Draw 14 Amps	Duty Cycle 70/30

POWERFUL ULTRA QUIET & OIL-FREE AIR COMPRESSOR

WITH 98% AIR DRYING SYSTEM AND AUTOMATIC DRAIN VALVE

PDP Performance Range
(-20° F. To -51° F.)
Air Quality:
ISO 8573 - Class 2.3.1

Powerful Twin 2.0 HP
(Total 4.0 HP)
Motor 1680 Rpm

One - Female Industrial
"Push To Connect"
Quick Connector

Two Pressure
Control Gauges

20 Gal.
Steel Air Tank

Automatic
Drain Valve

Air Dryer Cartridge
System - Up to 98% Dry Air

Oil-Free
Dual Piston Pump

3000+ Hour Life
Cycle Before Wear

Cleaner Air For
Better Tool Operation

Less Maintenance
And Costs

Aftercooler (Condenser)

BENEFITS

The CAT-20040DCADC Air Compressor has a Oil-Free Dual Piston pump designed to have a life cycle before wear of 3000 Plus hours.

To dry the air from the air compressor an Aftercooler and 98% Air Dryer are utilized. The aftercooler is a heat exchanger for cooling the discharge air from the air compressor. The water vapor from the compressed air is condensed into liquid form and pushed into the Air Dryer.

The easy to replace “Spin-On” Air Dryer Cartridge has a regenerating High-Temperature Molecular Sieve Desiccant to dry the air. This cartridge dryer has a life of 2-years before replacement.

The California Air Tools EZ-1 Automatic Drain Valve has been designed to eliminate manually draining your air compressor air tank. The manually set timer allows you to set the time for both the frequency and duration of the draining process.

Designed for the person looking for Power, 98% Dry Air with Low Dew Point Air Flow and Less Service with at Least 30% Less Noise!

Ideal for Dental, Milling, Surgical, Manufacturing Clean Rooms, Restaurant and General Engineering Applications.

SPECIFICATIONS

Specification	Details
Material	Alloy Steel
Color	White
Weight	170 Pounds
Height	30.5 inches
Item Dimensions L x W x H	37.5"L x 22"W x 30.5"H
Capacity	20 Gallons
Maximum Current	14 Amps
Voltage	220 Volts
Noise Level	75 dB

FEATURES

1. **Ultra Quiet – Only 75 decibels**
2. Oil-Free Pump (Class 1) – Cleaner air for better tool operation.
3. Less maintenance and Costs.
4. 0.01 Micron Prefilters (2 total)
5. 5.0 Micron (Class 2) Air Filter Regulator
6. Two pressure control gauges
7. One – Female industrial “Push to Connect” quick connector
8. Condor Pressure Switch

9. Thermal Overload Protector
10. 125 PSI Maximum Pressure
11. Working Pressure 90 PSI to 125 PSI (90 PSI default output; may be increased to 110 PSI)
12. 220 Volts / 60 Hertz / Single Phase – (No 208 Volts – if necessary, obtain 208 to 220 voltage booster)
13. Low Amp Draw – 14 Amps
14. Time to fill tank from empty to full – 150 Seconds
15. Recovery time from 95 PSI to 125 PSI – 40 Seconds
16. Duty Cycle – 70/30*
17. Less heat which dissipates more efficiently
18. 20 Gal. Steel Air Tank
19. L (37.1") x W/D (22") x H (30.5")
20. Weight: 170 lbs
21. 98% Air Dryer Cartridge uses a High-Temperature Molecular Sieve Desiccant
22. Easy to remove (spin off) and replace every 2 years (or 4000 motor running hours)
23. Aftercooler (condenser)
24. PDP performance range (-20' F. to -51' F.)
25. Air Quality: ISO 8573 – Class 2.3.1
26. 1 Year Limited Warranty
27. Comes complete (4) Air Filters
28. Plug Type: Nema 6-15P (fits Nema 6-15R or 6-20R receptacle)
29. EZ-1-2321 Auto Drain Valve Factory Installed
30. Commercial Use: Refer to State & City Codes
31. Non-ASME Air Tank
32. Assembled in USA with global components

Product Overview:

[California Air Tools 20040DCADC Website](#)

COMPATIBLE ACCESSORIES

- 16 Piece Air Hose & Air Tool Accessory Kit (CAT-376)
- California Air Tools Hybrider Flex 1/4in 25 Foot Hybrid Air Hose
- 317 Water (moisture) & Oil Separator Air Filter 1/4" NPT



Part Number		CAT-20040DCADC
UPC		850004451199
Shipping Dimensions		48"L x 40"W x 38"H
Shipping Weight		262 lbs
Shipping Class		85
Ship Type		Freight
Cage Code		7VRJ0
HTSUS		8414.80.1685
Country of Origin		MEXICO

CALIFORNIA AIR TOOLS | 8560 Siempre Viva Rd, San Diego, CA 92154, USA | (866) 409-4581 | info@californiaairtools.com